

PMS-PI Illumination Adapter Series

PMS-PI2404-4

- Short-circuit protection
- Manual control
- External trigger
- Grade display
- Power-down save
- RS232 control



Property introduction:

1. Adopt high integration digital circuit to control the average current in the constant current loop, to make sure the differences of LED under different given grade value of brightness minimized.
2. LCD Grade display, is more conducive to standardized operation of parameter, to improve the measurement efficiency.
3. Grade control of brightness has 1000 grades
4. Manual adjust model of combined rotation coding switch, highly improve the manual adjust efficiency and lengthen the span life of switch.
5. Isolate model RS232 Communication connector, support hot-pluggable, block damages from all kinds of ESD to the PC and instruments.
6. AC110-AC220 Wide range power input.
7. Accuracy of constant current is 5%, transfer efficiency highly reach to 95% or above.



- A CH1 Function of brightness increase/ decrease 1;
- B CH2 Function of brightness increase/ decrease 1;
- C CH3 Function of brightness increase/ decrease 1;
- D CH4 Function of brightness increase/ decrease 1;
- E Display
- F Power switch



- A. ZH 1 Output connector
- B. ZH 2 Output connector
- C. ZH 3 Output connector
- D. ZH 4 Output connector
- E. External trigger connector
- F. RS232 Communication connector
- G. Power input socket

Code	RS232 control	Channel	Output volts	Output current	Trigger function	Recommended load
PMS-PI2404-4	Yes	4	24V	400mA	Yes	2- 3 pcs of LED in series or in group