

# Bar Illumination Series

## Bar Illumination Series

- Light irradiation angle can be adjusted, multiple light sources can be combined
- Illumination range can from tens of millimeters to a few meters, and other specifications can also be made according to requirement.
- LED high-density arrangement, high brightness, color is optional

Code	Color	Size ( mm )	Voltage/Power/Red	Voltage/Power white/Power/Blue
PMS-BRL-38X11R/G/B/W	● ● ● ●	38mm X 11mm	24V/0.26W	24V/0.5W
PMS-BRL-56X15R/G/B/W	● ● ● ●	56mm X 15mm	24V/0.72W	24V/0.96W
PMS-BRL-90X19R/G/B/W	● ● ● ●	90mm X 19mm	24V/1.9W	24V/2.4W
PMS-BRL-112X42R/G/B/W	● ● ● ●	112mm X 42mm	24V/3.84W	24V/6.72W
PMS-BRL-140X19R/G/B/W	● ● ● ●	140mm X 19mm	24V/5.59W	24V/8.6W
PMS-BRL-170X20R/G/B/W	● ● ● ●	170mm X 20mm	24V/3.456W	24V/5.76W
PMS-BRL-210X19R/G/B/W	● ● ● ●	210mm X 19mm	24V/2.88W	24V/4.8W
PMS-BRL-270X42R/G/B/W	● ● ● ●	270mm X 42mm	24V/10.56W	24V/17.28W
PMS-BRL-380X40R/G/B/W	● ● ● ●	380mm X 40mm	24V/13W	24V/20W
PMS-BRL-470X40R/G/B/W	● ● ● ●	470mm X 40mm	24V/18.2W	24V/29W
PMS-BRL-580X40R/G/B/W	● ● ● ●	580mm X 40mm	24V/19.5W	24V/31W
PMS-BRL-770X57R/G/B/W	● ● ● ●	770mm X 57mm	24V/30.24W	24V/50.4W
PMS-BRL-900X26R/G/B/W	● ● ● ●	900mm X 26mm	24V/26W	24V/30W
PMS-BRL-1420X34R/G/B/W	● ● ● ●	1420mm X 34mm	24V/45.5W	24V/50W



## Application

- Precision measurement and edge detection to identify and inspection use
- Food processing and packaging lighting, packaging, testing and other
- Crack detection
- Inspect flatness of pin connector